

B O S T O N

Application	Roller Roman Panel
Composition	100% Polyester
Width	290cm 114 inches
Blockout Weight	410 gsm
Blockout Thickness	0.7 mm 0.028 inches
Translucent Weight	180 gsm
Translucent Thickness	0.5 mm 0.022 inches
Blockout Roll Size	20m 22yd
Translucent Roll Size	25m 27yd
Care Instructions	Do not allow dust to accumulate. Regularly gently vacuum with appropriate attachment. Do not wash. Do not dry clean. Warm iron if needed. Test in inconspicuous area with mild detergent solution prior to spot cleaning. Do not allow blind to become fully wet use damp cloth only.



WWW.WILSONFABRICS.COM.AU

WWW.WILSONFABRICS.COM

WHY WILSON FABRICS?



Australian Made

Made to protect you and your interior for many years to come.



PITCH BLACK™ Blockout Coating

Wilson Fabrics Blockout Coated fabrics are full blockout that surpass blockout standards.



StainProtect™

Protected by StainProtect™ which repel stains and spills.



Fade Resistant

Stringently tested for colourfastness to light ensuring they will stand the test of time.

Ultraviolet
Protection Factor



Excellent Protection
ARPANSA UPF RATING

UPF50+ Sun Protection

Highest UPF rating, providing "Excellent Protection" from the harmful ultraviolet radiation. Our fabrics let through 0.000 of UVA and 0.000 UVB rays ensuring quality protection from the sun, protecting you and your home.



PVC & Lead Free

Fabrics containing PVC and Lead can not only emit carcinogens in the home, the manufacturing process is also 'dirty' as toxic and carcinogenic components are required for manufacture. Hence why we only develop PVC and Lead Free Fabrics, better for you and the environment.



Fire Retardancy

Australian Standards only.
AS1530.3 Results available upon request.



5 Year Limited Warranty

Giving you peace of mind and long lasting quality.

DO YOU NEED MORE REASONS?

